

TDR 1100-11 RESIN US

Version 1.0 Revision Date: 11/12/2018 SDS Number: 400001010209 Date of last issue: -
 Date of first issue: 11/12/2018

SECTION 1. IDENTIFICATION

Product name : TDR 1100-11 RESIN US

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
 Address : P.O. Box 4980
 The Woodlands,
 TX 77387
 United States of America (USA)
 Telephone : Non-Emergency: (800) 257-5547
 E-mail address of person responsible for the SDS : SDS@huntsman.com
 Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Epoxy constituents
 Restrictions on use : For industrial use only.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Skin irritation : Category 2
 Eye irritation : Category 2A
 Skin sensitisation : Category 1
 Short-term (acute) aquatic hazard : Category 2
 Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :
 The image shows two GHS hazard pictograms: a red diamond with a black exclamation mark (Hazardous) and a red diamond with a black silhouette of a dead tree and fish (Environment).

Signal word : Warning

Hazard statements : H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.

TDR 1100-11 RESIN US

Version 1.0	Revision Date: 11/12/2018	SDS Number: 400001010209	Date of last issue: - Date of first issue: 11/12/2018
----------------	------------------------------	-----------------------------	--

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P391 Collect spillage.
Storage:
 Not available
Disposal:
 P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	90 - 100

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Treat symptomatically.
 Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.



TDR 1100-11 RESIN US

Version 1.0	Revision Date: 11/12/2018	SDS Number: 400001010209	Date of last issue: - Date of first issue: 11/12/2018
----------------	------------------------------	-----------------------------	--

- Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
 Halogenated compounds
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Refer to protective measures listed in sections 7 and 8.

TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in properly labelled containers.
- Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.
- Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

TDR 1100-11 RESIN US

Version 1.0	Revision Date: 11/12/2018	SDS Number: 400001010209	Date of last issue: - Date of first issue: 11/12/2018
----------------	------------------------------	-----------------------------	--

circumstance where air purifying respirators may not provide adequate protection.

- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : light cream
- Odour : mild
- Odour Threshold : No data is available on the product itself.
- pH : ca. 7 (68 °F / 20 °C)
Concentration: 500 g/l
- Freezing point : No data is available on the product itself.
- Melting point : No data is available on the product itself.
- Boiling point : > 392 °F / > 200 °C
Method: Information given is based on data obtained from similar substances.
- Flash point : > 351 °F / > 177 °C
Method: estimated, closed cup
- Evaporation rate : No data is available on the product itself.
- Flammability (solid, gas) : No data is available on the product itself.
- Flammability (liquids) : No data is available on the product itself.
- Upper explosion limit / Upper flammability limit : No data is available on the product itself.
- Lower explosion limit / Lower flammability limit : No data is available on the product itself.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



HUNTSMAN

Enriching lives through innovation

TDR 1100-11 RESIN US

Version 1.0 Revision Date: 11/12/2018 SDS Number: 400001010209 Date of last issue: -
Date of first issue: 11/12/2018

Vapour pressure : < 0.0001 hPa (77 °F / 25 °C)

Relative vapour density : No data is available on the product itself.

Relative density : 1.16 (77 °F / 25 °C)

Density : 1.16 g/cm³ (77 °F / 25 °C)

Solubility(ies)
Water solubility : practically insoluble (68 °F / 20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : None known.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicityComponents : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit
Assessment: Mild skin irritant
Method: OECD Test Guideline 404
Result: Irritating to skin.

Serious eye damage/eye irritation**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit
Result: Irritating to eyes.
Assessment: Mild eye irritant
Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Method: OECD Test Guideline 429

**TDR 1100-11 RESIN US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

Result: Causes sensitisation.

Assessment: No data available

Germ cell mutagenicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

Carcinogenicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 15 mg/kg
Frequency of Treatment: 7 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, male
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 days/week

TDR 1100-11 RESIN US

Version 1.0	Revision Date: 11/12/2018	SDS Number: 400001010209	Date of last issue: - Date of first issue: 11/12/2018
----------------	------------------------------	-----------------------------	--

Method: OECD Test Guideline 453
 Result: negative

Carcinogenicity - Assessment : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
 Species: Rat, male and female
 Application Route: Oral
 Dose: >750 milligram per kilogram
 General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
 General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
 Symptoms: No adverse effects
 Method: OECD Test Guideline 416
 Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
 Application Route: Dermal
 General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
 Method: Other guidelines
 Result: No teratogenic effects

Species: Rabbit, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level: 60 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Species: Rat, female

**TDR 1100-11 RESIN US**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks

Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 3 d

Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available



TDR 1100-11 RESIN US

Version 1.0	Revision Date: 11/12/2018	SDS Number: 400001010209	Date of last issue: - Date of first issue: 11/12/2018
----------------	------------------------------	-----------------------------	--

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 203

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: Fresh water

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: EPA-660/3-75-009

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic) : No data available



TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

toxicity)

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Biodegradability : Inoculum: Sewage (STP effluent)
 Concentration: 20 mg/l
 Result: Not readily biodegradable.
 Biodegradation: 5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Stability in water : Degradation half life(DT50): 4.83 d (77 °F / 25 °C) pH: 4
 Method: OECD Test Guideline 111
 Remarks: Fresh water

Degradation half life(DT50): 7.1 d (77 °F / 25 °C) pH: 9
 Method: OECD Test Guideline 111
 Remarks: Fresh water

Degradation half life(DT50): 3.58 d (77 °F / 25 °C) pH: 7
 Method: OECD Test Guideline 111
 Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
 Remarks: Does not bioaccumulate.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Partition coefficient: n-octanol/water : log Pow: 3.242 (77 °F / 25 °C)
 pH: 7.1
 Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:



TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

Distribution among environmental compartments : Koc: 445
 Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
 Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 Dispose of as hazardous waste in compliance with local and national regulations.
 Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.


TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA

UN/ID No.	: UN 3082
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964

IMDG

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations
DOT Classification

UN/ID/NA number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(BISPHENOL A EPOXY RESIN)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

TDR 1100-11 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/12/2018	400001010209	Date of first issue: 11/12/2018

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
1-chloro-2,3-epoxypropane	106-89-8	100	*
methanol	67-56-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

WARNING: This product can expose you to chemicals including 1-chloro-2,3-epoxypropane, which is/are known to the State of California to cause cancer, and 1-chloro-2,3-epoxypropane, 4,4'-isopropylidenediphenol, methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

CH INV : The formulation contains substances listed on the Swiss Inventory, On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511
FREEMAN

HUNTSMAN
Enriching lives through innovation


TDR 1100-11 RESIN US

Version 1.0 Revision Date: 11/12/2018 SDS Number: 400001010209 Date of last issue: -
Date of first issue: 11/12/2018

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Revision Date : 11/12/2018

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

SECTION 1. IDENTIFICATION

Product name : HARDENER 1100-11 US

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980
The Woodlands,
TX 77387
United States of America (USA)
Telephone : Non-Emergency: (800) 257-5547
E-mail address of person responsible for the SDS : SDS@huntsman.com
Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Inhalation) : Category 4
Skin corrosion : Category 1B
Serious eye damage : Category 1
Skin sensitisation : Category 1
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.

HARDENER 1100-11 US

 Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
 Date of first issue: 05/09/2019

Print Date 08/01/2019

Precautionary statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P363 Wash contaminated clothing before reuse.
 P391 Collect spillage.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Amines

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1	90 - 100
Diethylenetriamine	111-40-0	5 - 10
Triethylenetetramine	112-24-3	2.5 - 3
Silicon, amorphous	7631-86-9	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**



HUNTSMAN

Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : Consult a physician after significant exposure.
If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion : Carbon dioxide (CO₂)

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



HUNTSMAN

Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

- products Carbon monoxide
Nitrogen oxides (NOx)
- Specific extinguishing methods : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



HUNTSMAN

Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Material : Solvent-resistant gloves (butyl-rubber)
Material : Nitrile rubber
Material : Neoprene gloves
Material : PVC
Material : butyl-rubber
Break through time : 10 - 480 min

Material : Solvent-resistant gloves (butyl-rubber)
Material : Nitrile rubber
Material : Neoprene gloves
Material : PVC

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : ammoniacal

Odour Threshold : No data is available on the product itself.

pH : No data available

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : > 210 °F / > 99 °C
Method: estimated, closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : < 0.0001 hPa (77 °F / 25 °C)

Relative vapour density : No data is available on the product itself.

Relative density : 0.98

Density : 0.98 g/cm³ (77 °F / 25 °C)

Solubility(ies)
Water solubility : slightly soluble (68 °F / 20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : None known.

Incompatible materials : None known.

Hazardous decomposition products : carbon dioxide
carbon monoxide
Nitrogen oxides

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate: 3.7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Species: human skin

Method: OECD Test Guideline 431

Result: Non-corrosive

Species: human skin

Exposure time: 1 h

Assessment: Irritating to skin.

Method: OECD Test Guideline 439

Result: irritating

Diethylenetriamine:

Species: Rabbit

Assessment: Causes burns.

Result: Causes burns.

Triethylenetetramine:

Species: Rabbit

Assessment: Causes burns.

Method: OECD Test Guideline 404

Result: Causes burns.

Silicon, amorphous:

Species: Rabbit

Assessment: No skin irritation

Method: OECD Test Guideline 404

HARDENER 1100-11 US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/09/2019	400001008066	Date of first issue: 05/09/2019

Print Date 08/01/2019

Result: No skin irritation

Serious eye damage/eye irritation**Components:**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Species: Rabbit

Result: Severe eye irritation

Assessment: Risk of serious damage to eyes.

Method: OECD Test Guideline 405

Diethylenetriamine:

Species: Rabbit

Result: Corrosive

Assessment: Corrosive

Triethylenetetramine:

Species: Rabbit

Result: Corrosive

Assessment: Corrosive

Method: OECD Test Guideline 405

Silicon, amorphous:

Species: Rabbit

Result: No eye irritation

Assessment: No eye irritation

Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: Probability or evidence of high skin sensitisation rate in humans

Diethylenetriamine:

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

Remarks: Causes sensitisation.

Exposure routes: Respiratory Tract

Species: Mouse

Result: Does not cause respiratory sensitisation.

Triethylenetetramine:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
 Date of first issue: 05/09/2019

Print Date 08/01/2019

Exposure routes: Skin
 Species: Guinea pig
 Method: OECD Test Guideline 406
 Result: May cause sensitisation by skin contact.

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Assessment: May cause an allergic skin reaction.

Germ cell mutagenicity**Components:**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
 Test system: mouse lymphoma cells
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative

Test Type: Micronucleus test
 Test system: Human lymphocytes
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 487
 Result: negative

Test Type: Ames test
 Test system: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Triethylenetetramine:
 Genotoxicity in vitro

: Concentration: 0 - 200 µg/L
 Metabolic activation: negative
 Method: OECD Test Guideline 482
 Result: negative

Silicon, amorphous:
 Genotoxicity in vitro

: Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 473
 Result: negative

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Components:

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Diethylenetriamine:
Genotoxicity in vivo : Cell type: Somatic
Application Route: Oral
Dose: 85 - 850 mg/kg
Method: OECD Test Guideline 474
Result: negative

Application Route: Oral
Result: negative

Triethylenetetramine:
Genotoxicity in vivo : Application Route: Intraperitoneal injection
Dose: 0 - 600 mg/kg
Method: OECD Test Guideline 474
Result: negative

Silicon, amorphous:
Genotoxicity in vivo : Application Route: Inhalation
Dose: 50 mg/m³
Result: negative

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Germ cell mutagenicity-
Assessment : In vitro tests did not show mutagenic effects

Germ cell mutagenicity-
Assessment : No data available

Carcinogenicity

Components:

Diethylenetriamine:
Species: Mouse, male
Application Route: Dermal
Dose: 56.3 mg/kg
Frequency of Treatment: 3 daily
Result: negative

Triethylenetetramine:
Species: Mouse, male
Application Route: Dermal
Dose: 42 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 451
Result: negative

Species: Mouse, male
Application Route: Dermal
Exposure time: 104 weeks
Dose: 16.8 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 451

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
 Date of first issue: 05/09/2019

Print Date 08/01/2019

Silicon, amorphous:
 Species: Rat, male and female
 Application Route: Oral
 Exposure time: 103 weeks
 Dose: 1800 - 3200 mg/kg
 Frequency of Treatment: 7 daily
 Method: OECD Test Guideline 453
 Result: negative

Carcinogenicity - Assessment : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Components:**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Effects on fertility : Species: Rat, male and female
 Application Route: Oral
 Dose: 0, 100, 300, 1000 mg/kg bw/d
 Frequency of Treatment: 7 days/week
 General Toxicity - Parent: No observed adverse effect level:
 1,000 mg/kg body weight
 Method: OECD Test Guideline 422
 Result: Animal testing did not show any effects on fertility.

Diethylenetriamine: Species: Rat, male and female
 Application Route: Oral
 General Toxicity - Parent: No observed adverse effect level:
 30 mg/kg wet weight
 Method: OECD Test Guideline 421
 Result: positive

Components:

Diethylenetriamine: Effects on foetal development : Species: Rat
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 100 mg/kg body weight

HARDENER 1100-11 US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/09/2019	400001008066	Date of first issue: 05/09/2019

Print Date 08/01/2019

Method: OECD Test Guideline 421
Result: No adverse effects

Triethylenetetramine:

Species: Rat
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
> 750 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level:
125 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Silicon, amorphous:

Species: Mouse
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,340 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,350 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - : No data available
Assessment

STOT - single exposure**Components:**

Diethylenetriamine:
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

STOT - repeated exposure

No data available

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



HUNTSMAN

Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Repeated dose toxicity

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Species: Rat, male and female

NOAEL: 1000 mg/kg

NOAEL: 1,000 mg/kg

Application Route: Oral

Exposure time: 14 days

Number of exposures: Once daily

Dose: 0, 100, 300, 1000 mg/kg bw/d

Group: yes

Method: OECD Test Guideline 422

Target Organs: Liver

Diethylenetriamine:

Species: Rat, male and female

NOEC: 70 - 80 mg/m³

Application Route: Ingestion

Test atmosphere: vapour

Exposure time: 360 h

Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOAEL: 114 mg/kg/d

Application Route: Skin contact

Exposure time: 9,600 h

Number of exposures: 6 d

Method: Chronic toxicity

Triethylenetetramine:

Species: Rat, male and female

NOAEL: 50 mg/kg/d

Application Route: Ingestion

Exposure time: 26 Weeks

Number of exposures: 7 d

Method: Subchronic toxicity

Silicon, amorphous:

Species: Rat, male and female

NOAEL: 7950 - 8980 mg/kg

Application Route: Ingestion

Exposure time: 4,320 h

Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

: 4000 - 4500 mg/m³

Application Route: Ingestion

Test atmosphere: dust/mist

Exposure time: 13 Weeks

Number of exposures: 7 d

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Method: OECD Test Guideline 413

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Repeated dose toxicity - Assessment : No adverse effect has been observed in chronic toxicity tests.

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Diethylenetriamine:

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Toxicity to fish : LC50: 430 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.1.

Triethylenetetramine:
Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 330 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: Fish Acute Toxicity Test

Silicon, amorphous:
Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7.07 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Diethylenetriamine:
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 32 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Triethylenetetramine:
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 31.1 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.2.

Silicon, amorphous:
Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 4.34 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water

HARDENER 1100-11 US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/09/2019	400001008066	Date of first issue: 05/09/2019

Print Date 08/01/2019

Method: OECD Test Guideline 201

EC10 (Selenastrum capricornutum (green algae)): 1.78 mg/l
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

Diethylenetriamine:
 Toxicity to algae/aquatic plants : EbC50 (Selenastrum capricornutum (green algae)): 1,164 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

Triethylenetetramine:
 Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l
 Exposure time: 72 h
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

Silicon, amorphous:
 Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) - Product : 1
 1

Components:

Diethylenetriamine:
 Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
 Exposure time: 28 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 210

Components:

Diethylenetriamine:
 Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 5.6 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: Directive 67/548/EEC, Annex V, C.20

Triethylenetetramine:
 Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 1.9 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

M-Factor (Chronic aquatic toxicity) : No data available

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Toxicity to microorganisms : EC50 (activated sludge): 384 mg/l
Exposure time: 3 h
Test Type: static test
Method: OECD Test Guideline 209

Triethylenetetramine:

Toxicity to microorganisms : EC50 (activated sludge): 800 mg/l
Exposure time: 0.5 h
Test Type: static test
Test substance: Fresh water

Components:

Diethylenetriamine:

Toxicity to soil dwelling organisms : EC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg
Exposure time: 56 d
Method: OECD Test Guideline 222

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment

Components:

Diethylenetriamine:

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability**Components:**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 - 70 %
Exposure time: 74 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Diethylenetriamine:
Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Biodegradation: 87 %
Exposure time: 21 d
Method: OECD Test Guideline 301D

Triethylenetetramine:
Biodegradability : Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 162 d
Method: OECD Test Guideline 301D

Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 84 d
Method: Inherent Biodegradability: Modified SCAS Test

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Stability in water : No data available

Components:

Diethylenetriamine:
Photodegradation : Test Type: Air
Rate constant: 500000
Degradation (direct photolysis): 50 %

Impact on Sewage Treatment : No data available

Bioaccumulative potential

Components:

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Bioaccumulation : Bioconcentration factor (BCF): 77.4
Remarks: Does not bioaccumulate.

Diethylenetriamine:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 0.3 - 6.3
Exposure time: 42 d
Test substance: Fresh water
Method: flow-through test
Remarks: Bioaccumulation is unlikely.

Components:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine:

Partition coefficient: n-octanol/water : log Pow: 10.34
Method: OECD Test Guideline 117

Diethylenetriamine:

Partition coefficient: n-octanol/water : log Pow: -1.58 (68 °F / 20 °C)
pH: 7

Triethylenetetramine:

Partition coefficient: n-octanol/water : log Pow: -2.65 (68 °F / 20 °C)
Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:

Diethylenetriamine:

Distribution among environmental compartments : Koc: 19111

Triethylenetetramine:

Distribution among environmental compartments : Koc: 1584.9 - 5012
Method: OECD Test Guideline 106

Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**

HUNTSMAN
Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and
national regulations.
Dispose of contents/ container to an approved waste disposal
plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA

UN/ID No. : UN 2735
Proper shipping name : Amines, liquid, corrosive, n.o.s.
(DIETHYLENE TRIAMINE, TRIETHYLENE TETRAMINE)
Class : 8
Packing group : II
Labels : Corrosive
Packing instruction (cargo
aircraft) : 855
Packing instruction
(passenger aircraft) : 851

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



HUNTSMAN

Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

IMDG

UN number : UN 2735
Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(DIETHYLENE TRIAMINE, TRIETHYLENE TETRAMINE)
Class : 8
Packing group : II
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

DOT Classification

UN/ID/NA number : UN 2735
Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(DIETHYLENE TRIAMINE, TRIETHYLENE TETRAMINE)
Class : 8
Packing group : II
Labels : CORROSIVE
ERG Code : 153
Marine pollutant : yes(POLYAMIDE RESIN)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 FREEMAN



HUNTSMAN

Enriching lives through innovation

HARDENER 1100-11 US

Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
Date of first issue: 05/09/2019

Print Date 08/01/2019

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

CH INV : The formulation contains substances listed on the Swiss Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

HARDENER 1100-11 US


Version 1.0 Revision Date: 05/09/2019 SDS Number: 400001008066 Date of last issue: -
 Date of first issue: 05/09/2019

Print Date 08/01/2019

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

- Revision Date : 05/09/2019
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA Z-3 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

SAFETY DATA SHEET

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511  FREEMAN

 **HUNTSMAN**

Enriching lives through innovation

HARDENER 1100-11 US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/09/2019	400001008066	Date of first issue: 05/09/2019

Print Date 08/01/2019

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.