



Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

1 Identification

· Product identifier

· Trade name: EC-433 (A) Resin

· Article number: 657081

· Application of the substance / the mixture Epoxy resin

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

advanced.resins.ehs@us.sika.com

· Manufacturer/Supplier:

Manufacturer:

Sika Advanced Resins

30800 Stephenson Hwy

Madison Heights

MI 48071

USA

· Information department: Product safety department

· Emergency telephone number:

During normalopening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 1A H350 May cause cancer.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.



GHS05 Corrosion

Eye Damage 1 H318 Causes serious eye damage.



Skin Irritation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 1)

· Hazard pictograms







GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

 $Trimethylol\ propane\ triglycidyl\ ether\ copolymer$

Quartz (SiO2)

1,4-bis(2,3-epoxypropoxy)butane

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 3Reactivity = 0

(Contd. on page 3)





Page 3/12

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

· HMIS-ratings (scale 0 - 4)

HEALTH *3 Health = *3 Fire = 3 REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous compone	· Dangerous components:		
CAS: 30499-70-8	Trimethylol propane triglycidyl ether copolymer	≥3-<5%	
CAS: 2425-79-8 EINECS: 219-371-7	1,4-bis(2,3-epoxypropoxy)butane	1-5%	
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO2)	0.1-1%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)





Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- \cdot Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	16 mg/m³
14808-60-7	Quartz (SiO2)	0.075 mg/m^3
· PAC-2:		
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	170 mg/m^3
14808-60-7	Quartz (SiO2)	33 mg/m ³
· PAC-3:		
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	220 mg/m³
14808-60-7	Quartz (SiO2)	200 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 5)





Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eves and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)







Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and	l chemical	l properties
----------------	------------	--------------

· Information on basic physical and chemical properties

· General Information

 $\cdot Appearance:$

Form: Pasty
Color: Grey

Odor: Amine-like
Odor threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: >200 °C (>392 °F)

Flash point: 94 °C (201.2 °F)

· Flammability (solid, gaseous): Not applicable.

• Auto igniting: $400 \, ^{\circ}C \, (752 \, ^{\circ}F)$

· Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapor pressure: Not determined.

• Density at 20 °C (68 °F): $1.85 \text{ g/cm}^3 (15.44 \text{ lbs/gal})$

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

(Contd. on page 7)







Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

		(Contd. of page 6)
Kinematic:	Not determined.	
· Solvent content: VOC content:	4.00 % 74.2 g/l / 0.62 lb/gal	
Solids content:	60.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

 Oral
 LD50
 2,000 mg/kg (rat)

 Dermal
 LD50
 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
14808-60-7 Quartz (SiO2)	1
· NTP (National Toxicology Program)	
14808-60-7 Quartz (SiO2)	K
	(Contd. on page 8)







Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Trans	nort	info	rmation
I I I I Cores		und or	Intertori

77X7 X7-----1----

· UN-Number · DOT · IMDG, IATA	not regulated UN3082
· UN proper shipping name · DOT · IMDG	As stated below: not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin), MARINE POLLUTANT

(Contd. on page 9)







Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

	(Contd. of page
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUIL N.O.S. (Epoxy phenol novolac resin)
Transport hazard class(es)	
DOT	
Class	not regulated
IMDG, IATA	
1 1 1 1 1 1 1 1 1 1	
Class	9 Miscellaneous dangerous substances and articles
Label	9
Packing group	
DOT	not regulated
IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	Yes
G . I . I . (7.171.)	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
EMS Number:	F- A , S - F
Stowage Category	A
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
-	LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN), 9, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

7429-90-5 aluminum powder (stabilised)

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 10)





Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 9)

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

14808-60-7 Quartz (SiO2)

A2

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Trimethylol propane triglycidyl ether copolymer

Quartz (SiO2)

1,4-bis(2,3-epoxypropoxy)butane

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 10)

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 03/10/2023
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

(Contd. on page 12)







Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC-433 (A) Resin

(Contd. of page 11)

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation – Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Carcinogenicity 1A: Carcinogenicity – Category 1A
Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

* Data compared to the previous version altered.







Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

1 Identification

- · Product identifier
- · Trade name: EC433-2 Fast Hardener
- · Article number: 657082
- · Application of the substance / the mixture Epoxy resin
- · Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

advanced.resins.ehs@us.sika.com

· Manufacturer/Supplier:

Manufacturer:

Sika Advanced Resins

30800 Stephenson Hwy

Madison Heights

MI 48071

USA

- · Information department: Product safety department
- · Emergency telephone number:

During normalopening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Toxicity - Oral 3 H301 Toxic if swallowed.



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corrosion 1B

H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 1)

· Hazard pictograms







GHS05 GHS06

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenebis(cyclohexylamine)

diethylmethylbenzenediamine

· Hazard statements

Toxic if swallowed.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *3
Fire = 1
Reactivity = 1

 $\overline{\mathsf{REACTIVITY}_{\boxed{0}}} \ \ Reactivity = 0$

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)







Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 2)

· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1761-71-3 EINECS: 217-168-8	4,4'-methylenebis(cyclohexylamine)	50-100%
CAS: 68479-98-1 EINECS: 270-877-4	diethylmethylbenzenediamine	10-20%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- $\cdot \textit{After inhalation:} \ \textit{In case of unconsciousness place patient stably in side position for transportation.}$
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

(Contd. on page 4)







Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

None of the ingredients is listed.

· PAC-2:

None of the ingredients is listed.

· *PAC-3*:

 $None\ of\ the\ ingredients\ is\ listed.$

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

US



Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

US







Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 5)

Information on basic physical and	chemical properties	
General Information		
Appearance:	** **	
Form:	Liquid	
Color:	Amber colored	
Odor: Odor threshold:	Amine-like Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	>100 °C (>212 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	420 °C (788 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	0.97 g/cm³ (8.09 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wat	ter): Not determined.	
Viscosity:		
<i>Dynamic at 20 °C (68 °F):</i>	150 mPas	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	





Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

 Oral
 LD50
 625 mg/kg (rat)

 Dermal
 LD50
 2,100 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)

LIS







Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

96 hr LC50 | 46-100 mg/l (Fish)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

	UN-	Num	ber
--	-----	-----	-----

· IMDG

· DOT, IMDG, IATA UN2922

· UN proper shipping name

• **DOT** Corrosive liquids, toxic, n.o.s. (Cycloaliphatic Amine)

CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine,

diethylmethylbenzenediamine), MARINE POLLUTANT

(Contd. on page 9)

US





Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

	(Contd. of pag
IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine)
Transport hazard class(es)	
DOT	
CORPOSIVE TOXIC TOXIC	
Class	8 Corrosive substances
Label	8, 6.1
IMDG	
Class	8 Corrosive substances
Label	8/6.1
Class Label	8 Corrosive substances 8 (6.1)
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substance diethylmethylbenzenediamine
Marine pollutant:	Yes
-	Symbol (fish and tree)
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	
EMS Number: Stowage Category	F-A,S-B B
Stowage Category Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L

(Contd. on page 10)







Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

	(Contd. of page 9
· Remarks:	Special marking with the symbol (fish and tree).
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 2922 CORROSIVE LIQUID, TOXIC, N.O.S. (CYCLOALIPHATIC AMINE), 8 (6.1), II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 10)

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05 GHS06

303 011300

OHS

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenebis(cyclohexylamine)

diethylmethylbenzenediamine

· Hazard statements

Toxic if swallowed.

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)





Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023 Reviewed on 03/10/2023

Trade name: EC433-2 Fast Hardener

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact
- · Date of preparation / last revision 03/10/2023
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Eye Damage 1: Serious eye damage/eye irritation - Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

* * Data compared to the previous version altered.

US