

CORPORATE HEADQUARTERS 5700 Skylab Road Huntington Beach, CA 92647 PHONE: (714) 899-8100 FAX: (714) 899-8179 Internet: www.airtechonline.com e-mail: airtech@airtechintl.com

> Page 7 18 October, 2004



DATA SHEET

Dahlar[®] Release Bag 125

Economical Vacuum Bag and Release Film

Description


Dahlar[®] Release Bag 125 is an economical film designed for both vacuum bagging and release film applications. Dahlar[®] Release Bag 125 can be used for cures up to 285°F (140°C) and will release from most resins associated with aerospace, marine, and recreational products. This formulation has improved tear resistance and elongation over products previously offered as low temperature, multiple process films. Dahlar[®] Release Bag 125 is the ideal release film for polyester or vinyl ester resins as well as epoxies and phenolics. All standard perforations available.

Dahlar[®] Release Bag 125 is also offered with our embossed, cracked ice pattern making it a breather, release film and vacuum bag all-in-one.

Standard roll sizes:				
Thickness	Width	Length	Approximate Weight	
Inches (µm)	Inches (cm)	Feet (m)	lbs. (kg)	
.002 (50)	60 (152.4)	2000 (610)	103 (47)	
.002 (50)	*120 (305)	1000 (305)	103 (47)	
*Shipped as centerfold				
Embossed roll size:				
Thickness	Width	Length	Approximate Weight	
Inches (µm)	Inches (cm)	Feet (m)	lbs. (kg)	
.002 (50)	60 (152.4)	1000 (305)	52 (24)	
Physical Characteristics:				
Color:		Green		
Elongation:		400%		
Maximum Recommended Use		285°F		
Temperature (1)		(140°C)		
Shelf life: 1		18 months fro	18 months from date of shipment	

NOTES: (1) Maximum recommended use temperature is dependent upon the duration at maximum temperature and is process specific. Airtech recommends testing prior to use.

CATALOG POSITION: BAGGING FILMS



any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes.