SAFETY DATA SHEET



1. Identification

Product identifier	Liq Hdr, .75Oz Mekp		
Other means of identification Product Code	30018		
Recommended use	Liquid Hardener, Polymer Rea	ction Catalyst	
Manufacturer/Importer/Supplier/ Manufacturer		,	
Company name Address	Quest Automotive Products 600 Nova Drive SE Massillon, OH 44646 United States		
Telephone E-mail	General Assistance rpandrus@quest-ap.com	(330) 830-60	00
Contact person Emergency phone number	Ron Andrus CHEMTREC	(800) 424-930	00
2. Hazard(s) identification			
Physical hazards	Flammable liquids		Category 3
	Organic peroxides		Type D
Health hazards	Acute toxicity, oral		Category 4
	A outo tovicity inholotion		Catagory

		.) = =
Health hazards	Acute toxicity, oral	Category
	Acute toxicity, inhalation	Category
	Skin corrosion/irritation	Category
	Serious eye damage/eye irritation	Category
	Specific target organ toxicity, repeated exposure	Category
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Hazard statement

Precautionary statement Prevention

Flammable liquid and vapor. Heating may cause a fire. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. Fatal if inhaled. May cause damage to organs through prolonged or repeated exposure.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep/Store away from clothing and other combustible materials. Keep container tightly closed. Keep only in original container. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment is urgent (see this label). Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.



Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Protect from sunlight. Store at temperatures not exceeding 25°C / 77°F. Keep cool. Store away from other materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	63% of the mixture consists of component(s) of unknown acute oral toxicity. 64.5% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butanone peroxide		1338-23-4	30 to <40
2-butanone		78-93-3	1 to <5
Hydrogen peroxide		7722-84-1	1 to <5
Other components below reportable le	evels		60 to <70

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.	
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.	
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.	
Most important symptoms/effects, acute and delayed	Abdominal pain. Burning pain and severe corrosive skin damage. Diarrhea. Nausea, vomiting. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Prolonged exposure may cause chronic effects.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.	
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.	
General fire hazards	Flammable liquid and vapor. Heating may cause a fire.	



6. Accidental release measures

o. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe vapors or spray mist. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Keep away from clothing and other combustible materials. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Keep only in the original container. Store in a well-ventilated place. Store away from other materials. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value 2-butanone (CAS 78-93-3) PEL 590 mg/m3 200 ppm Hydrogen peroxide (CAS PEL 1.4 mg/m3 7722-84-1) 1 ppm **US. ACGIH Threshold Limit Values** Components Value Type 2-butanone (CAS 78-93-3) STEL 300 ppm 200 ppm TWA 2-Butanone peroxide (CAS Ceiling 0.2 ppm 1338-23-4) Hydrogen peroxide (CAS TWA 1 ppm 7722-84-1) **US. NIOSH: Pocket Guide to Chemical Hazards** Components Type Value 2-butanone (CAS 78-93-3) STEL 885 mg/m3 300 ppm TWA 590 mg/m3 200 ppm



Components		Туре	Va	alue
2-Butanone peroxide (CAS 1338-23-4)		Ceiling	1.	5 mg/m3
,			0.2	2 ppm
Hydrogen peroxide (CAS 7722-84-1)		TWA	1.4	4 mg/m3
			1	ppm
iological limit values				
ACGIH Biological Exposu	re Indices			
Components	Value	Determinant	Specimen	Sampling Time
2-butanone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
* - For sampling details, ple	ase see the sour	ce document.		
	maintain airt established,	orne levels below recom	mended exposur to an acceptable	tilation, or other engineering controls to e limits. If exposure limits have not been level. Eye wash facilities and emergency
ndividual protection measure	s, such as pers	onal protective equipme	ent	
Eye/face protection	Wear safety	glasses with side shields	(or goggles) and	l a face shield.
Skin protection				
	Wear approv	ariata abamiaal reaistant .		
Hand protection	supplier.	onate chemical resistant (gloves. Suitable g	ploves can be recommended by the glove
Other	supplier.	priate chemical resistant o		ploves can be recommended by the glove
	supplier. Wear approp		clothing.	
Other	supplier. Wear approp Wear positiv	priate chemical resistant of	clothing. I breathing appar	ratus (SCBA).

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	66.2 °F (19 °C) estimated
Flash point	140.0 °F (60.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.04 hPa estimated
Vapor density	Not available.



Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	140 °F (60 °C)
Viscosity	Not available.
Other information	
Density	8.32 lbs/gal
Flammability class	Combustible IIIA estimated
Percent volatile	2.5 % estimated
Specific gravity	1
VOC	1.5 % estimated
10. Stability and reactivity	/
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Sunlight. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Combustible material.
Hazardous decomposition	No hazardous decomposition products are known.

Hazardous decomposition	No hazardous decomposition products are known.
products	

11. Toxicological information

Information on likely routes of exposure

Inhalation	Fatal if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Abdominal pain. Burning pain and severe corrosive skin damage. Diarrhea. Nausea, vomiting. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Information on toxicological effects

Acute toxicity Fatal if inhaled. Harmful if swallowed.		
Components	Species	Test Results
2-butanone (CAS 78-93-3)		
Acute		
Dermal		
LD50	Rabbit	> 8000 mg/kg
Inhalation		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours
Oral		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg



Components	Species	Test Results		
2-Butanone peroxide (CAS 1338-	23-4)			
<u>Acute</u>				
Inhalation				
LC50	Mouse	170 mg/l, 4 Hours		
	Rat	200 mg/l, 4 Hours		
Oral				
LD50	Rat	6.86 ml/kg		
* Estimates for product may b	be based on additional compone	nt data not shown.		
Skin corrosion/irritation	Causes severe skin burns ar	d eye damage.		
Serious eye damage/eye irritation	Causes serious eye damage			
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
IARC Monographs. Overall	Evaluation of Carcinogenicity			
Hydrogen peroxide (CAS		3 Not classifiable as to carcinogenicity to humans.		
OSHA Specifically Regulate Not listed.	ed Substances (29 CFR 1910. [/]	001-1050)		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
Specific target organ toxicity -	Not classified.			
single exposure	Not oldosined.			
Specific target organ toxicity - repeated exposure	May cause damage to organ	through prolonged or repeated exposure.		
Aspiration hazard	Not an aspiration hazard.			
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation m be harmful.			

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

	pecciancy	and ange of negative opine can have a han		
Components	Species		Test Results	
2-butanone (CAS 78-93-3)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	4025 - 6440 mg/l, 48 hours	
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-o	ctanol / water (log Kow)	
2-butanone	0.29	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispo contents/container in accordance with local/regional/national/international regulations.	ose of
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Material name: Liq Hdr, .75Oz Mekp		SDS



Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

DOT	
UN number	UN3105
UN proper shipping name	Organic Peroxide Type D, Liquid (Methyl Ethyl Ketone Peroxide <45%)
Transport hazard class(es)	
Class	5.2
Subsidiary risk	-
Packing group	Not applicable.
	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	152
ΙΑΤΑ	
UN number	UN3105
UN proper shipping name	Organic Peroxide Type D, Liquid (Methyl Ethyl Ketone Peroxide <45%)
Transport hazard class(es)	
Class	5.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
IMDG	
UN number	UN3105
UN proper shipping name	Organic Peroxide Type D, Liquid (Methyl Ethyl Ketone Peroxide <45%)
Transport hazard class(es)	
Class	5.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-J, S-R
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT; IATA	







15. Regulatory information

15. Regulatory In	iormation	1				
US federal regulation	IS	Standard, 2	9 CFR 1910.120		d by the OSHA Hazard (ory List.	Communication
TSCA Section 12	2(b) Export N	Notification (40 CFR 707, Su	ıbpt. D)		
Not regulated	J.					
CERCLA Hazard	ous Substar	nce List (40	CFR 302.4)			
2-butanone (CAS 78-93-3)			Listed.			
2-Butanone peroxide (CAS 1338-23-4) SARA 304 Emergency release notification				Listed.		
Hydrogen pe OSHA Specifical	•	,	s (29 CFR 1910	1000 LBS . 1001-1050)		
Not listed.						
Superfund Amendme	ents and Rea	authorizatio	n Act of 1986 (S	SARA)		
Hazard categorie		Immediate Delayed Ha Fire Hazaro Pressure H	Hazard - Yes azard - Yes I - Yes			
SARA 302 Extre	mely hazard	ous substar	nce			
Chemical name	CAS	S number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Hydrogen peroxid	le 772	2-84-1	1000	1000 lbs		
SARA 311/312 H chemical	azardous	No				
SARA 313 (TRI ro Not regulated						
Other federal regulat	ions					
Clean Air Act (C		112 Hazardo	ous Air Pollutai	nts (HAPs) List		
Not regulated Clean Air Act (C		112(r) Accid	lental Release I	Prevention (40 CFR 6	8.130)	
Not regulated		.,		·	·	
Safe Drinking Wa (SDWA)	ater Act	Not regulate	ed.			
Drug Enforc Chemical Co			DEA). List 2, Es	sential Chemicals (21	CFR 1310.02(b) and 1	310.04(f)(2) and
	one (CAS 78-			6714		
			DEA). List 1 & 2	Exempt Chemical Mi	xtures (21 CFR 1310.1	2(c))
2-butanc DEA Exemp	one (CAS 78- t Chemical N		le Number	35 %WV		
2-butanc	one (CAS 78-	93-3)		6714		
US state regulations						
US. California Co	ontrolled Su	bstances. C	A Department o	of Justice (California	Health and Safety Cod	e Section 11100)
Not listed						

Not listed.



US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-butanone (CAS 78-93-3)

US. Massachusetts RTK - Substance List

2-butanone (CAS 78-93-3) 2-Butanone peroxide (CAS 1338-23-4) Hydrogen peroxide (CAS 7722-84-1)

US. New Jersey Worker and Community Right-to-Know Act

2-butanone (CAS 78-93-3) 2-Butanone peroxide (CAS 1338-23-4) Hydrogen peroxide (CAS 7722-84-1)

US. Pennsylvania Worker and Community Right-to-Know Law

2-butanone (CAS 78-93-3) 2-Butanone peroxide (CAS 1338-23-4) Hydrogen peroxide (CAS 7722-84-1)

US. Rhode Island RTK

2-butanone (CAS 78-93-3) 2-Butanone peroxide (CAS 1338-23-4) Hydrogen peroxide (CAS 7722-84-1)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-17-2015
Version #	01
HMIS® ratings	Health: 4* Flammability: 3 Physical hazard: 3
NFPA ratings	Health: 4 Flammability: 3 Instability: 3
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

