

## Chemlease® Sealer 2697

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

### SECTION 1. IDENTIFICATION

Product name : Chemlease® Sealer 2697

#### Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP  
1445 W McPherson Park Dr  
PO Box 860, Howell MI 48844-0860  
United States  
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com  
Emergency telephone number : +1 517 545 7070

#### Recommended use of the chemical and restrictions on use

Recommended use : Release agent  
Restrictions on use : For industrial use only.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2  
Skin irritation : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.



**Chemlease® Sealer 2697**

Version 1.0      Revision Date: 02/24/2023      Date of last issue: -  
Date of first issue: 02/24/2023      Print Date: 08/18/2023

May cause drowsiness or dizziness.

Precautionary statements

- : **Prevention:**  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.  
In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.
- Storage:**  
Store in a well-ventilated place. Keep cool.
- Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), light alkylate	64741-66-8	Trade secret ( $\geq 30 - < 60$ )
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Trade secret ( $\geq 30 - < 60$ )
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Trade secret ( $\geq 5 - < 10$ )

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- If inhaled : Call a physician or poison control centre immediately. Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.

**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,  
for at least 10 minutes.  
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Never give anything by mouth to an unconscious person.  
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Central nervous system depression  
Can be absorbed through skin.  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.  
Aspiration may cause pulmonary oedema and pneumonitis.  
Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema
- Notes to physician : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during : Do not let product enter drains.

**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

- firefighting : Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to health.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Non-sparking tools should be used.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Advice on safe handling : Use only in an area containing explosion proof equipment.  
Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.

**Chemlease® Sealer 2697**

Version 1.0	Revision Date: 02/24/2023	Date of last issue: - Date of first issue: 02/24/2023	Print Date: 08/18/2023
----------------	------------------------------	--	---------------------------

For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Ensure all equipment is electrically grounded before beginning transfer operations.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
Do not enter areas where used or stored until adequately ventilated.  
Do not repack.  
Do not re-use empty containers.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Keep container closed when not in use.

Conditions for safe storage : Store in original container.  
Keep container closed when not in use.  
Keep in a cool place away from oxidizing agents.  
Keep in a dry, cool and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with the particular national regulations.  
Keep in properly labelled containers.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), light alkylate	64741-66-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)

**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

**Engineering measures** : Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : colourless

Odour : amine-like

Odour Threshold : No data available

pH : Not applicable



**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

Melting point/range : No data available

Boiling point/boiling range : 257 °F / 125 °C

Flash point : 46 °F / 8 °C  
Method: Setaflash, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 20 hPa (68 °F / 20 °C)  
(for a component of this mixture)

Relative vapour density : No data available

Relative density : 0.74 (68 °F / 20 °C)  
Reference substance: Water  
The value is calculated

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s (104 °F / 40 °C)

Explosive properties : Not explosive



**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

Oxidizing properties : No data available  
Sublimation point : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazards to be specially mentioned.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.  
Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.  
Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

**Product:**

Acute oral toxicity : Remarks: Effects due to ingestion may include:  
Symptoms: Central nervous system depression  
Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.  
Irritating to respiratory system.  
Symptoms: Inhalation may provoke the following symptoms: Local irritation, Respiratory disorders, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression  
Acute dermal toxicity : Symptoms: Redness, Local irritation

**Components:**

**Naphtha (petroleum), light alkylate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

**Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg





**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

**Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

**Skin corrosion/irritation**

**Product:**

Remarks : Irritating to skin.

**Components:**

**Naphtha (petroleum), light alkylate:**

Result : Skin irritation

**Naphtha (petroleum), hydrotreated heavy:**

Result : Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

**Product:**

Remarks : Irritating to eyes.

**Respiratory or skin sensitisation**

**Product:**

Remarks : This information is not available.

**Germ cell mutagenicity**

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Carcinogenicity**

**Product:**

Remarks : No data available

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**IARC  
OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is



**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**STOT - single exposure**

**Components:**

**Naphtha (petroleum), light alkylate:**

Assessment : May cause drowsiness or dizziness.

**Repeated dose toxicity**

**Product:**

Remarks : This information is not available.

**Aspiration toxicity**

**Product:**

May be fatal if swallowed and enters airways.

**Components:**

**Naphtha (petroleum), light alkylate:**

May be fatal if swallowed and enters airways.

**Naphtha (petroleum), hydrotreated heavy:**

May be fatal if swallowed and enters airways.

**Naphtha (petroleum), hydrotreated heavy:**

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.



**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

**Components:**

**Naphtha (petroleum), light alkylate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 18.4 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.4 mg/l  
Exposure time: 48 h

**Naphtha (petroleum), hydrotreated heavy:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

**Product:**

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

**Components:**

**Naphtha (petroleum), light alkylate:**

Biodegradability : Result: Not readily biodegradable.

**Naphtha (petroleum), hydrotreated heavy:**

Biodegradability : Result: Not readily biodegradable.

**Naphtha (petroleum), hydrotreated heavy:**

Biodegradability : Result: Readily biodegradable.

**Bioaccumulative potential**

**Product:**

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

**Components:**

**Naphtha (petroleum), light alkylate:**

Bioaccumulation : Bioconcentration factor (BCF): 105

Partition coefficient: n-octanol/water : log Pow: 3.52

**Naphtha (petroleum), hydrotreated heavy:**

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

**Naphtha (petroleum), hydrotreated heavy:**

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

**Mobility in soil**

**Product:**

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological information : Toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and  
national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as  
the unused product.  
Dispose of waste product or used containers according to  
local regulations.

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Hydrocarbons, C7-C9, isoalkanes, hexamethyldisiloxane)  
Class : 3  
Packing group : II

**Chemlease® Sealer 2697**

Version 1.0	Revision Date: 02/24/2023	Date of last issue: - Date of first issue: 02/24/2023	Print Date: 08/18/2023
----------------	------------------------------	--	---------------------------

Labels : 3

**IATA-DGR**

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.  
(Hydrocarbons, C7-C9, isoalkanes, hexamethyldisiloxane)

Class : 3

Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo aircraft) : 364

Packing instruction (passenger aircraft) : 353

**IMDG-Code**

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Hydrocarbons, C7-C9, isoalkanes, hexamethyldisiloxane)

Class : 3

Packing group : II

Labels : 3

EmS Code : F-E, S-E

Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

UN/ID/NA number : UN 1993

Proper shipping name : Flammable liquids, n.o.s.  
(Hydrocarbons, C7-C9, isoalkanes, hexamethyldisiloxane)

Class : 3

Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 128

Marine pollutant : yes

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION**

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Specific target organ toxicity (single or repeated exposure)

**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

Aspiration hazard

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

---

**SECTION 16. OTHER INFORMATION**

**Further information**

**Full text of other abbreviations**

NIOSH REL : USA. NIOSH Recommended Exposure Limits  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1  
Limits for Air Contaminants  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour  
workday during a 40-hour workweek  
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded  
at any time during a workday  
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous



**Chemlease® Sealer 2697**

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/24/2023	Date of first issue: 02/24/2023	08/18/2023

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/24/2023

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.